

B11/B12/B13/B14/B16 Injector Adjust Shim Technical File

SKU: L20000B2BKMS600



B11/B12/B13/B14/B16 Injector Adjust Shim Technical File**Content**

1. B11/B12/B13/B14/B16 Injector Adjust Shim Introduction	2
1.1. B11/B12/B13/B14/B16 Injector Adjust Shim Basic Information	2
1.2. B11/B12/B13/B14/B16 Injector Adjust Shim Common Part Number	2
1.3. B11/B12/B13/B14/B16 Injector Adjust Shim Parameter	2
1.4. B11/B12/B13/B14/B16 Injector Adjust Shim Specifications And Dimensions	2
1.5. B11/B12/B13/B14/B16 Injector Adjust Shim Quality Control	3
1.6. B11/B12/B13/B14/B16 Injector Adjust Shim Customized Service	3
1.7. B11/B12/B13/B14/B16 Injector Adjust Shim Packing List and Package Size	4
1.8. B11/B12/B13/B14/B16 Injector Adjust Shim Testing Standard and Certificate	5
1.9. B11/B12/B13/B14/B16 Injector Adjust Shim Warranty Instructions	6
1.10. B11/B12/B13/B14/B16 Injector Adjust Shim Manufacturer	7
2. B11/B12/B13/B14/B16 Injector Adjust Shim Technical Support	7
2.1. B11/B12/B13/B14/B16 Injector Adjust Shim Installation	7
2.2. B11/B12/B13/B14/B16 Injector Adjust Shim Not Working Normally	8
2.3. B11/B12/B13/B14/B16 Injector Adjust Shim Causes of Being Damaged	8
2.4. B11/B12/B13/B14/B16 Injector Adjust Shim Technical Support Obtaining Methods	9
3. B11/B12/B13/B14/B16 Injector Adjust Shim Purchase and Delivery	9
3.1. B11/B12/B13/B14/B16 Injector Adjust Shim Purchase Payment Term	9
3.2. B11/B12/B13/B14/B16 Injector Adjust Shim Main Sales Markets	9
3.3. B11/B12/B13/B14/B16 Injector Adjust Shim Declaration Requirements	9
3.4. B11/B12/B13/B14/B16 Injector Adjust Shim Shipping Ways	10
3.5. B11/B12/B13/B14/B16 Injector Adjust Shim Lead Time	10
3.6. B11/B12/B13/B14/B16 Injector Adjust Shim Logistics Time for Destination Out of China's Areas	10
3.7. B11/B12/B13/B14/B16 Injector Adjust Shim Packing	11
4. B11/B12/B13/B14/B16 Injector Adjust Shim Storage Standard	12
5. Company Information	12
5.1. Company Introduction	13
5.2. Salesmen's Contact Information	13
6. Copyright Statement	14

B11/B12/B13/B14/B16 Injector Adjust Shim Technical File**1. B11/B12/B13/B14/B16 Injector Adjust Shim Introduction****1.1. B11/B12/B13/B14/B16 Injector Adjust Shim Basic Information**

Title	B11/B12/B13/B14/B16 Injector Adjust Shim	Quality
SKU1	L20000B2BKMS600	China Made New

1.2. B11/B12/B13/B14/B16 Injector Adjust Shim Common Part Number**(1) Injector Adjust Shim Exchange Information**

Injector Part Number	Injector Part Number	Injector Part Number	Injector Part Number
0445110454	0445110646	0445110318	0445110629

(2) Injector Adjust Shim Application Information

Brand	Model	Engine	OE Number
JMC	/	/	11112100ABA
AUDI	A1 2.0 TDI	CFHB	03L 130 277 Q
SEAT	Alhambra 2.0 TDI	CFFE	03L 130 277 Q
SKODA	Octavia 2.0 TDI	CLCA	03L 130 277 Q
DONGFENG	/	Yunnei 4D19TCI	X0445110318

(3) Injector Adjust Shim Common Writing

B11/B12/B13/B14/B16

1.3. B11/B12/B13/B14/B16 Injector Adjust Shim ParameterAdaptation System: **Common Rail System**Injector Adjust Shim Series: **CRI2**Injector Adjust Shim Type: **Electromagnetic****1.4. B11/B12/B13/B14/B16 Injector Adjust Shim Specifications And Dimensions**

Injector Adjust Shim Thickness: B11: (0.9-1.5) B12: (0.9-1.5) B13: (1.0-1.96) B14: (1.00-1.86) B16: (1.11-1.20) B22: (0.98-1.44) B25: (0.9-1.2) B26: (1.34-1.76) B27: (1.5-1.72) B31: (1.2-1.3)

Injector Adjust Shim Net Weight: **6g**Injector Adjust Shim Gross Weight: **600g**Injector Adjust Shim Quality: **China Made New**Injector Adjust Shim Package Size: **31*cm*23cm *2cm**Injector Adjust Shim Type: **High Pressure Common Rail Injector Adjust Shim**

Injector Adjust Shim MOQ: 500pcs

1.5. B11/B12/B13/B14/B16 Injector Adjust Shim Quality Control

(1) Injector Adjust Shim Testing

All injector adjust shim parts are tested for electrical characteristics, accuracy, high temperature, low temperature, pressure resistance, leakage, durability, and various working conditions.

(2) Injector Adjust Shim Assembling

In addition, injector adjust shim production and installation process quality control, our company strictly follows the standard product installation data and product installation steps for installation, such as injector adjust shim stroke test, injector adjust shim solenoid valve tightening torque.

(3) Injector Adjust Shim Inspection

The injector adjust shim factory inspection is tested three times: full inspection, random inspection, and batch inspection. The injector adjust shim factory inspection will use different brands of test benches to test the same injector adjust shim for a total of no less than three times. The injector adjust shim installation and testing environment is completed in a dust-free workshop.

1.6. B11/B12/B13/B14/B16 Injector Adjust Shim Customized Service

(1) Injector Adjust Shim Customized Service Coverage: Meet the customized needs of OEM manufacturers for shell lettering, logo engraving, injector adjust shim internal packaging, injector adjust shim external packaging and labels customized, etc.



Injector Adjust Shim Packaging

(2) Injector Adjust Shim Customized Service Requirements:

The sales of customized injector adjust shim products shall not be less than **10 units**.

The packaging of customized injector adjust shims shall not be less than **1000 pieces**.

Customized products involve the need of specify logo, the OEM manufacturer needs to provide trademark authorization and the sample of logo image file.

⚠ **Once the customized injector adjust shim is sold, it cannot be returned or exchanged if there are no quality problems.**

1.7. B11/B12/B13/B14/B16 Injector Adjust Shim Packing List and Package Size

(1) Injector Adjust Shim Spare Parts List

No.	1	2	3
Image			
Name	Injector Adjust Shim Size	Injector Adjust Shim Thickness	Injector Adjust Shim Accuracy
Description	B11: ($\Phi 19 \times S22$) B12: ($\Phi 18 \times S22$) B13: ($\Phi 2.3 \times \Phi 4.2$) B14: ($\Phi 3.4 \times \Phi 5.56$) B16: ($\Phi 2.28$)	B11: (0.9-1.5) B12: (0.9-1.5) B13: (1.0-1.96) B14: (1.00-1.86) B16: (1.11-1.20)	0.01/0.02 gear
No.	4	5	6
Image			
Name	Desiccant	White Bubble Bag	White anti-rust bag
Description	Prevents plunger from rusting; absorbs moisture	Prevent adjust shim from being damaged by external forces	Prevent adjustment shim from rusting

⚠ Minors are prohibited from using the injector adjust shim assembly, O-rings, fuel inlet protective cover, injector adjust shim housing cover, fuel return cover, VCI anti-rust bag, and bubble bag to avoid personal injury.

⚠ O-rings and adjust shim are disposable installation accessories and need to be replaced for reinstallation.

⚠ Nozzle protective cover, injector adjust shim housing cover, and fuel return cover are recyclable accessories and can be recycled.

⚠ VCI anti-rust bag and bubble bag are non-degradable materials. Please dispose of them properly after use.

⚠ The injector adjust shim and installation parts guide tube should be treated with appropriate sealing fuel during installation

(2) Injector Adjust Shim Packing Size



No.	Name	Injector Adjust Shim Packing Size (cm)
1	Injector Adjust Shim Box	34*14*7

1.8. B11/B12/B13/B14/B16 Injector Adjust Shim Testing Standard and Certificate

Shumatt can provide the factory quality inspection test report of each injector adjust shim to ensure that each injector adjust shim delivered meets the engine performance indicators.

BOTEN		测试报告		4.05.2019 10:42:09																																																	
承办单位: _____																																																					
电话: _____ 地址: _____																																																					
传真: _____ 联系人: _____																																																					
客户地址: _____																																																					
电话: _____ 检测单位: _____																																																					
传真: _____ 客户姓名: _____																																																					
检测地址: _____																																																					
设计名称: _____ 检测部: _____																																																					
型号/零件号: _____																																																					
检测内容: _____																																																					
检测结果																																																					
报告编号: C00002-0515																																																					
<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th style="width: 15%;">检测项目</th> <th style="width: 15%;">检测结果</th> <th style="width: 15%;">标准值/范围</th> <th style="width: 15%;">判定</th> <th style="width: 15%;">检测员/日期</th> <th style="width: 10%;"></th> </tr> </thead> <tbody> <tr> <td>LEAK TEST:</td> <td>3.0</td> <td>— 0 —</td> <td>OK</td> <td>20.04.19</td> <td>✓</td> </tr> <tr> <td>Back:</td> <td>3.0</td> <td>4</td> <td>NG</td> <td>20.04.19</td> <td>✓</td> </tr> <tr> <td>MAXIM:</td> <td>3.0</td> <td>12.5 ± 0.5</td> <td>C</td> <td>20.04.19</td> <td>✗</td> </tr> <tr> <td>Max:</td> <td>29.5</td> <td>28.5 ± 1.4</td> <td>C</td> <td>20.04.19</td> <td>✓</td> </tr> <tr> <td>TL:</td> <td>28.4</td> <td>24.0 ± 0.5</td> <td>C</td> <td>20.04.19</td> <td>✓</td> </tr> <tr> <td>EL:</td> <td>14.1</td> <td>15.0 ± 0.8</td> <td>C</td> <td>20.04.19</td> <td>✓</td> </tr> <tr> <td>VE:</td> <td>4.7</td> <td>4.5 ± 1.0</td> <td>C</td> <td>20.04.19</td> <td>✓</td> </tr> </tbody> </table>						检测项目	检测结果	标准值/范围	判定	检测员/日期		LEAK TEST:	3.0	— 0 —	OK	20.04.19	✓	Back:	3.0	4	NG	20.04.19	✓	MAXIM:	3.0	12.5 ± 0.5	C	20.04.19	✗	Max:	29.5	28.5 ± 1.4	C	20.04.19	✓	TL:	28.4	24.0 ± 0.5	C	20.04.19	✓	EL:	14.1	15.0 ± 0.8	C	20.04.19	✓	VE:	4.7	4.5 ± 1.0	C	20.04.19	✓
检测项目	检测结果	标准值/范围	判定	检测员/日期																																																	
LEAK TEST:	3.0	— 0 —	OK	20.04.19	✓																																																
Back:	3.0	4	NG	20.04.19	✓																																																
MAXIM:	3.0	12.5 ± 0.5	C	20.04.19	✗																																																
Max:	29.5	28.5 ± 1.4	C	20.04.19	✓																																																
TL:	28.4	24.0 ± 0.5	C	20.04.19	✓																																																
EL:	14.1	15.0 ± 0.8	C	20.04.19	✓																																																
VE:	4.7	4.5 ± 1.0	C	20.04.19	✓																																																

☐ 检测前
 ☐ 重检测

☐ 检测后

1.9. B11/B12/B13/B14/B16 Injector Adjust Shim Warranty Instructions

(1) Product Warranty Conditions and Instructions

It is necessary to provide pictures, videos, or test reports detected by the injector adjust shim inspection equipment when the injector adjust shim is abnormal during use as evidence to feed back to the salesman.

Abnormal conditions are properly explained such as: 1.Smoke, 2. Engine shake, 3. Difficulty starting the engine, 4. Engine noise, 5. Fuel leakage etc.

(2) Injector Adjust Shim Warranty Coverage

Within 15 days after customer receives the B11/B12/B13/B14/B16 injector adjust shim, if there is a performance failure and the product has no appearance damage, customer can choose to replace it or repair it;

If the B11/B12/B13/B14/B16 injector adjust shim has performance problems during the warranty period (6-12 months), and it is confirmed that it is product's problems after testing, you can contact our salesmen to replace the same model or a reworked product with the same performance for free;

If the injector adjust shim house has obvious scratches, it can only be repaired and it will be returned as it is if the product is confirmed to be fault-free.

⚠️ Tips: For products not covered by warranty, our company can provide paid maintenance services. For products after paid repaired, the same performance problem will have a free warranty period within 3 months from the date of repairing.

(3) Injector Adjust Shim Out of Warranty Coverage

- ① The warranty period has expired and is not covered by the warranty.

- ② Injector adjust shim failure caused by high temperature, high pressure, humidity, rain and snow, saline-alkali land, earthquake, and abnormal environment.
- ③ The customer privately disassembles or repairs the injector adjust shim, causing the injector adjust shim to be damaged.
- ④ Injector adjust shim damage caused by human factors (throwing, strong magnetic field magnetization, arson).
- ⑤ Injector adjust shim failure or injector adjust shim damage caused by non-injector adjust shim design, technology, manufacturing, quality and other issues.
- ⑥ Injector adjust shim failure caused by system pressure exceeding the approved system pressure.
- ⑦ Injector adjust shim failure caused by system voltage exceeding the approved voltage.
- ⑧ Impurities (water, lead, aluminum powder, iron powder, sulfide) in the system fuel exceed the standard requirements and cause injector adjust shim failure.
- ⑨ Injector adjust shim failure caused by not installing according to the tightening torque specified in the vehicle engine maintenance manual (tightening torque is too large or too small).
- ⑩ Injector adjust shim failure caused by failure to follow the installation angle specified in the vehicle engine maintenance manual.
- 11 Injector adjust shim failure caused by failure to comply with the cleaning requirements specified in the vehicle engine maintenance manual.
- 12 Injector adjust shim failure caused by failure to replace wearing parts in accordance with the requirements specified in the vehicle engine maintenance manual.
- 13 Injector adjust shim failure is caused by not following the intake system clearance and exhaust system clearance requirements specified in the vehicle engine maintenance manual.
- 14 Injector adjust shim failure is caused by not replacing the wearing parts of the fuel intake system and the clearance between the fuel intake system pipeline and the injector adjust shim connection specified in the vehicle engine maintenance manual.

1.10. B11/B12/B13/B14/B16 Injector Adjust Shim Manufacturer

Injector Adjust Shim Manufacturer: Shenzhen Shumatt Technology Co., Ltd

2. B11/B12/B13/B14/B16 Injector Adjust Shim Technical Support

2.1. B11/B12/B13/B14/B16 Injector Adjust Shim Installation

(1) B11/B12/B13/B14/B16 Injector Adjust Shim Installation Precautions:

▲ The replacement of the injector adjust shim must strictly follow the electrical system, the approved pressure of the low-pressure fuel intake system, the approved pressure of the high-pressure fuel circuit system, and fuel system replacement consumables requirements (including the low-pressure fuel circuit system filter and the high-pressure fuel circuit) specified in the vehicle engine maintenance manual.

▲ Replacement of wearing parts of the fuel system, cleaning requirements for the connection between the fuel system and the injector adjust shim, the fitting clearance of the injector adjust shim connection, the installation angle and tightening torque of the injector adjust shim, the fitting clearance of the intake system, and the fitting clearance of the exhaust system to ensure the service life of the engine and the normal operation of the injector adjust shim.

⚠ When installing the injector adjust shim on the engine, it is necessary to clean the engine cylinder block, cylinder head and other parts connected to the injector adjust shim and ensure that they are clean and free of dust, carbon deposits, water, rust spots, etc.

⚠ Failure to replace the new sealing ring gasket may lead to: injector adjust shim deformation, fuel leakage, air leakage, serious damage to the injector adjust shim, causing the injector adjust shim to break and cause engine damage.

⚠ When installing the injector adjust shim on the engine, please carefully check that the parts related to the installation of the injector adjust shim, such as the injector adjust shim pressure plate, screws, push rods and other accessories are not deformed, and strictly follow the operating procedures in the engine maintenance manual for installation.

⚠ It is forbidden to expose the injector adjust shim for a long time in an environment with severe dust pollution and corrosion to iron products.

⚠ It is forbidden to expose the injector adjust shim for a long time in a strong magnetic field environment.

2.2. **B11/B12/B13/B14/B16** Injector Adjust Shim Not Working Normally

- (1) There is air in the fuel circuit of the engine fuel system.
- (2) The vehicle injector adjust shim supply system is abnormal.
- (3) The engine common rail system is leaking or the pressure limiting valve is damaged.
- (4) The wiring harness connecting the vehicle to the injector adjust shim is short-circuited, disconnected, or has poor contact.
- (5) The anti-rust fuel of the injector adjust shim solidifies after being left for a long time, causing the internal components to become stuck or the fuel holes to become clogged.

⚠ Before installing, carefully check whether other components in the common rail system except the injector adjust shim are damaged to prevent the injector adjust shim from not working properly after being replaced.

2.3. **B11/B12/B13/B14/B16** Injector Adjust Shim Causes of Being Damaged

- (1) Didn't operate properly according to engine maintenance manual during disassembly or installation, resulting in damage to the injector adjust shim.
- (2) The fuel used for the vehicle does not meet the standard cause damage to the injector adjust shim, such as: the water content in the fuel exceeds the standard, iron powder, aluminum powder, sulfide impurities exceed the standard, etc.
- (3) The engine is not regularly maintained according to the engine maintenance manual (please refer to the vehicle maintenance manual for the maintenance mileage). For example, failure to replace the lubricating fuel of the engine system for a long time will cause abnormal wear of the engine, excessive exhaust gas volume or a large amount of carbon deposits inside the engine. The filter is not replaced

during maintenance or the replaced filter cannot reach the original filter standard. all above reasons can cause damage to the injector adjust shim.

- (4) The abrasion of the injector adjust shim produces iron powder and aluminum powder enter the injector adjust shim and cause damage to the injector adjust shim.
- (5) The deformation and abrasion of fuel tank result in iron powder or aluminum powder entering the injector adjust shim and causing damage to the injector adjust shim.
- (6) The injector adjust shim is damaged due to replacement or adjustment of the relevant parts of the injector adjust shim. For example, the valve clearance does not meet the standard after the engine is repaired, the replacement or modification of the wiring harness connected to the injector adjust shim fails to meet the original standard.
- (7) The engine is overheated and overloaded for a long-time working result in damage to the injector adjust shim.
- (8) The injector adjust shim will be damaged naturally at the end of its working life.
- (9) The injector adjust shim is magnetized (injector adjust shim parts' magnetic exceeded) causing the injector adjust shim to not work properly.

⚠ Before replacing the injector adjust shim, please check the engine parts carefully according to the engine maintenance manual to avoid the injector adjust shim being damaged again after replacement.

2.4. B11/B12/B13/B14/B16 Injector Adjust Shim Technical Support Obtaining Methods

- (1) Injector adjust shim technical file, visit <http://shumatt.com> to get the technical file.
- (2) Injector adjust shim technical videos

Facebook: Follow <https://www.facebook.com/hison.lito> get technical support videos, and stay tuned for more information.

YouTube: https://www.youtube.com/channel/UCByvYBx7VjV_mAfxh_Hu-aw to get the technical videos, constantly follow can get more information.

Shumatt: Visit <http://shumatt.com> to get the technical videos.

- (3) Injector adjust shim information query software

TruckBook Parts EPC APP, Android/Apple App Store download and install, visit <http://shumatt.com> to get the download and installation tutorial

- (4) Search the injector adjust shim test data through TruckBook Parts EPC APP.

3. B11/B12/B13/B14/B16 Injector Adjust Shim Purchase and Delivery

3.1. B11/B12/B13/B14/B16 Injector Adjust Shim Purchase Payment Term

Payment Terms: T/T, PayPal, Alipay, WeChat

⚠ Please contact our salesmen for specific payment information.

3.2. B11/B12/B13/B14/B16 Injector Adjust Shim Main Sales Markets

Injector Adjust Shim Main Sales Markets: Asia, Europe, North America, South America, Africa etc.

3.3. B11/B12/B13/B14/B16 Injector Adjust Shim Declaration Requirements

Shumatt can assist customers to provide the following documents for import customs clearance: contract, invoice, packing list, bill of lading, insurance policy, certificate of origin, etc.

3.4. B11/B12/B13/B14/B16 Injector Adjust Shim Shipping Ways

Destination in China Areas: SF Express, Debon Express, the corresponding logistics company can be provided according to customer requirements in special cases.

Destinations Out of China's Areas: DHL, UPS, FedEx, TNT air, ocean or other shipping methods required by customers.

3.5. B11/B12/B13/B14/B16 Injector Adjust Shim Lead Time

Lead Time: Send out within 3 – 7 working days after receiving payment (Except for special products and special cases) .

3.6. B11/B12/B13/B14/B16 Injector Adjust Shim Logistics Time for Destination Out of China's Areas

DHL Logistics Time:

Country or Region of Departure	Hong Kong, China	Other Countries or Regions of Asia	Australia and New Zealand	Europe	America	Other Countries
China's Mainland	7 Days	7 Days	8 Days	8 Days	8-12 Days	7-10 Days

UPS Logistics Time: Country or Region of Departure: China's Mainland

Country of Destination	Estimated Arrival Time	Country of Destination	Estimated Arrival Time	Country of Destination	Estimated Arrival Time
Japan	3 Days	UK	5-7Days	Egypt	5-7 Days
Turkey	5-7 Days	Singapore	3 Days	Switzerland	5-7 Days
Bahrain	5-7 Days	Latvia	7-10 Days	New Zealand	7-10 Days
Sri Lanka	5-7 Days	Thailand	3 Days	Austria	5-7 Days
Romania	5-7 Days	Vietnam	3-5 Days	Estonia	5-7 Days
Malaysia	3-5 Days	Israel	5-7 Days	Mexico	7-10 Days
France	5-7 Days	America	5-7 Days	United Arab Emirates	5-7 Days
Italy	5-7 Days	Netherlands	5-7 Days	Bengal	7-10 Days
Lebanon	5-7 Days	Philippine	3-5 Days	Greece	7-10 Days
South Korea	3 Days	Spain	5-7 Days	Myanmar	5-7 Days
Canada	5-7 Days	Germany	5-7 Days	Saudi Arabia	7-10 Days
Portugal	5-7 Days	Australia	5-7 Days	South Africa	7-10 Days
Denmark	5-7 Days	Belgium	5-7 Days	Ukraine	7-10 Days
India	7-10 Days	Qatar	7-10 Days	Poland	5-7 Days
Indonesia	3-5 Days	Morocco	7-10 Days	Pakistan	7-10 Days
Kuwait	7-10 Days	/	/	/	/

⚠ The logistics time is for reference only and is subject to the actual arrival.

Mob/Whatsapp: +86 13410541523

Email : ruby@shumatt.com

© 2025 Shenzhen Shumatt Technology Co., Ltd

Tel: +8675523215133

Website : www.shumatt.com

3.7. B11/B12/B13/B14/B16 Injector Adjust Shim Packing

Domestic Express Packaging: Usually wrapped in waterproof scotch tape, such as picture No. 1.

International Express Packaging: Wrapped with waterproof yellow tape After wrapping the black protective film, such as picture No. 2.

Pallet Shipping: Use fumigation free and recycling trays that meet export requirements, and use white wrapping protective film to wrap and bind with cable ties for the outside, such as picture No. 3, also, the products can be packaged according to customers' requirements.


⚠ The packing tray is made of plastic and can be recycled.

⚠ Transparent tape, yellow tape, black wrapping protective film, white wrapping protective film are non-degradable materials, please dispose of them properly.

⚠ Minors are prohibited from using transparent tape, yellow tape, black wrapping protective film, and white wrapping protective film to avoid personal injury.



Pic No. 1



Pic No. 2

Domestic express packaging:
Wrapped with Transparent tape

International express packaging:
Wrapped with yellow tape after wrapping black protective film



Pallet shipment: Use pallets that meet export requirements and wrap with white plastic wrap and tie.

4. B11/B12/B13/B14/B16 Injector Adjust Shim Storage Standard

(1) Choose a Suitable Storage Place

The warehouse and cargo yard where the injector adjust shim is stored should be kept clean and dry, and away from the factory buildings that generate harmful gases and dust; do not mix with acids, alkali, salt, and other substances; the storage place should have a good drainage system; the cargo yard should be flattened with gravel or furnace ash etc. to enhance the water permeability of the surface layer to keep the reservoir area dry.

(2) Strict Requirements of Warehousing

Strict inspections should be carried out when the injector adjust shim are put into storage, the surface cleaning work should be done well to remove water traces, fuel stains, ashes, and other dirt, remove the rust and do anti-rust treatment in time. Packaged injector adjust shim must be protected from damage.

(3) Keep The Warehouse Dry And Preventing Moisture

The relative humidity is usually below 70% for the injector adjust shim placed in the room, and the corrosion of the injector adjust shim is significantly reduced.

injector adjust shim must be stored in the warehouse, and they are forbidden to store in the same warehouse with commodities with high water content.

(4) Stack Properly

After the injector adjust shim is exposed to rain, the corrosion rate will increase significantly. The purpose of sealing is to isolate the injector adjust shim from rainwater and humid air, so the warehouse window should be checked in time to avoid rainwater entering the warehouse.

If the injector adjust shim package is damaged, it should be repaired or replaced; when the package is damp, the packaging material should be dried; if the original anti-corrosion and fuel applied at the factory is found to be damaged or dried up, it should be cleaned and re-applied fuel in time.

⚠ It is forbidden to leave the injector adjust shim exposed in the air for a long time.

⚠ It is forbidden to store acids, alkalis, salts, and other substances together with the injector adjust shim.

⚠ The unpacked injector adjust shim must be rust-proof during secondary storage.

5. Company Information



5.1. Company Introduction

Chinese Name: 深圳市舒马特科技有限公司

English Name: Shenzhen Shumatt Technology Co., Ltd

 **Mob Phone/WeChat:** +86-13410541523

 **HK Telephone:** +852-67653519

 **Telephone:** +86-755-23215133

 **Email:** ruby@shumatt.com

 **Website:** www.shumatt.com

 **Shenzhen Office:** 11-12, Floor 14, Building 13, Qinchengda Building, Exit A, Honglang North Subway Station, Bao'an District, Shenzhen, China's Mainland

 **Shenzhen Office:** Exit C, Qiao Touxu Metro Station, NO. 66 Chongqing Road, Fuhai Avenue, Bao'an District, Shenzhen, China Mainland

 **Hong Kong Office:** Jianfa Street Industrial Zone, Tuen Mun, New Territories, Hong Kong, China

 **After-sales Service Address:** Please contact our salesmen to obtain and provide the corresponding product maintenance reasons. (Reference: [1.9. B11/B12/B13/B14/B16 Injector Adjust Shim Warranty Instructions](#))

5.2. Salesmen's Contact Information

Mob/Whatsapp: +86 13410541523

Email : ruby@shumatt.com

© 2025 Shenzhen Shumatt Technology Co., Ltd

Tel: +8675523215133

Website : www.shumatt.com

No.	Name	WeChat/WhatsApp	Email
1	Ruby	+86-13410541523	ruby@shumatt.com
2	Ivy	+86-18025299821	sales@shumatt.com
3	Rebecca	+86-18025349821	sales01@shumatt.com
4	Janny	+86-18028749821	sales02@shumatt.com
5	Sam	+86-13316859821	Sales8@shumatt.com
6	Natalie	+86- 18938945856	sales15@shumatt.com
7	Ada	+86-1342286353	sales5@shumatt.com
8	Hison Li	+86-18318811871	web@shumatt.com
9	Mecca	+86-18938948618	sales11@shumatt.com
10	Eric	+86 18319033618	sales3@shumatt.com
11	Wayne (Joaquín en español)	+86-13316959821	wayne@shumatt.com
12	Sylvia	+86 18312499884	sales6@shumatt.com
Visit http://shumatt.com to obtain the latest information of salesmen			
PS: Shumatt's salesmen's emails are all end with @shumatt.com			

6. Copyright Statement

The copyright of any contents (including but not limited to parameters, data, text, charts, images, sounds, or videos, etc.) provided in "**B11/B12/B13/B14/B16 Injector Adjust Shim Technical File**" belong to Shenzhen Shumatt Technology Co., Ltd. Without the prior written permission of Shenzhen Shumatt Technology Co., Ltd., you are not allowed to modify any contents in "**B11/B12/B13/B14/B16 Injector Adjust Shim Technical File**" in any way. At the same time, any conditions to spread, repost, display the contents of "**B11/B12/B13/B14/B16 Injector Adjust Shim Technical File**" should indicate that the cited article is from Shenzhen Shumatt Technology Co., Ltd., Any actions failure to follow above conditions to use "**B11/B12/B13/B14/B16 Injector Adjust Shim Technical File**" will violate the "Copyright Law of the People's Republic of China" and other laws and regulations and the provisions of relevant international conventions.